

EAST - [10027638.wsp:1]

Tools Window Help

Drafts  
 Pending  
 Active  
 L1: (66617) "455"/S.ccls.  
 L2: (9343) 1 and ("local oscillator" or LO)  
 L3: (1081) 2 and (downconversion or downconvert\$3)  
 L4: (973) 3 and (RF or "radio frequency")  
 L5: (423) 4 and "baseband signal"  
 L6: (52) 5 and ("in phase" and quadrature)  
 L7: (33) 6 and (sum and difference)  
 L8: (20) 6 and (sum and difference)  
 L9: (12) 8 and "second frequency"  
 L10: (0) 9 and (different near8 "second frequency")  
 L11: (11) 9 and (different near8 frequency)  
 Failed  
 Saved  
 Favorites  
 Tagged (3)  
 UDC  
 Queue  
 Trash

DBs: US-PG-PUB:USPAT:EPD  
 Default generator: OR  
 Highlight all hit terms initially

9 and (different near8 frequency)

BRS form IS&R form Image Text HTML

	U	1	Document ID	Issue Date	Pages	Title	Current OR	Current X	Reti	Inventor	S
1	<input type="checkbox"/>	<input checked="" type="checkbox"/>	US 6671500 B2	20031230	24	Frequency plan	455/118	455/112; 455/113		Damgaard, Morten et al.	<input checked="" type="checkbox"/>
2	<input type="checkbox"/>	<input checked="" type="checkbox"/>	US 6377315 B1	20020423	85	System and method for providing a low power receiver design	348/726	257/E27.046		Carr, Frank et al.	<input checked="" type="checkbox"/>
3	<input type="checkbox"/>	<input checked="" type="checkbox"/>	US 5914944 A	19990622	19	Method of improving efficiency of radio channel usage in overlapping co	370/320	370/321; 370/354;		Haugli, Hans-Christian et al.	<input checked="" type="checkbox"/>